

MAGNARAY® International



- Standard finish
- Clear anodized aluminum
- Colors available

WEATHERPROOF

W1PL36 W Series Fixture

VISUALLY EFFICIENT LIGHTING PRODUCTS

MODEL	TYPE	MOUNTING	SHIPPING WT.	PACKAGE
W1PL36	Single 36 watt	Conduit	7 lbs.	1



SPECIFICATIONS

REFLECTOR	Precision-formed, highly polished aluminum reflector, scientifically shaped to produce optical magnification. 125.332 sq. in. of reflecting surface.
LENS	Water Clear acrylic lens is break-resistant, will not discolor in sunlight, permits maximum light transmission. Gasketed. Clear Lexan® available.
HOUSING	Clear anodized aluminum with cast aluminum ends, blends with landscape and surroundings. Furnished with 360° conduit type swivels.
ELECTRICAL SPECIFICATIONS	Standard 120 Volt/60 Hz magnetic or electronic ballast. Also available in 277 Volt/60 Hz, 220 Volt/50 Hz, and 12 VDC.
ADAPTATIONS	Easy surface mounting.

DIMENSIONS				
Measure	A	B	C	D
Inches	5"	6-1/2"	2-1/2"	18-3/4"
MM	127	165	63	476



P.O. Box 990 / Bradenton, FL 34206-0990
 FON: (941) 755-2111
 WEB: www.magnaray.com

2242 Whitfield Park Loop / Sarasota, FL 34243
 FAX: (941) 751-5483
 EMail: sales@magnaray.com